RampRack | Bike Rack

SPECIFICATIONS

MaxRack System

RampRack is a high density semi-vertical bike rack that requires minimal lifting. Slip the front wheel into the curved wheel cradle and roll the bike up the ramp. Individual ramps are staggered in high and low positions to increase density and can be attached directly to walls or MaxRack Stands. The RampRack can also be used in combination with MaxRack Hangers. Semi-Vertical Bike Rack: High density

- Heavy-duty construction
- 2 solid steel lock bars to secure frame and both wheels
- Integrates with MaxRack System
- Indoor/outdoor use



RR-L & RR-H (x3)

GENERAL INFORMATION

Frame: 1/8" x 1 1/2" Steel Angle

Ramp: 11 Gauge Steel Channel

Lock Bars: 5/8" Dia. Solid Steel Rod

Finish: Powder Coated TGIC Polyester Paint RAL 9005/Jet Black Custom colors available


Max Tire Width: 2 1/2"

Installation: Anchor securely to level, cement floor *and* to masonry wall, cement wall or MaxRack Stand; Stagger ramp positions (high/low) Ceiling Height: 7' min. required

DIMENSIONS/CAPACITY

RampRack	Length	Width	Height	Spacing	Bikes
RR-H (High ramp)	4"	47 ½"	72"	15"	1
RR-L (Low ramp)	4"	47 ½"	60"	15"	1
RR-TB2 (Tie Bar)					


Alternate High/Low ramps when abutting units



L

FRONT

RampRacks can be secured to floor individually Optional: Tie Bar (RR-TB2) (connects 2 ramps)



SIDE

MaxRack System is comprised of modular bike racks and mounting fixtures that offer interchangeability with a cohesive aesthetic.

MODULAR BIKE RACKS: MaxRack Hanger (vertical) RampRack (semi-vertical)

MaxRack System

MODULAR FIXTURES: MaxRack Wall Bracket MaxRack Stand (1 or 2-sided)



MaxRack Stand w/Ramps



MaxRack Wall Bracket w/Ramps



MaxRack Stand w/MaxRacks & RampRacks

888-995-8090



BIKE PARKING SOLUTIONS Bike Shelters | Bike Racks | Bike Storage Systems

32 Ann Street Clifton, NJ 07013 info@velodomeshelters.com www.velodomeshelters.com